



DECLARATION OF PERFORMANCE No. 133-CPR-2024

1. Unique identification code:

Self-adhesive underlayer bitumen membrane

NEXLER Stick (2024/1)

2. Intended use or uses:

- waterproofing of roofs, which is the subject to fire reaction test,
- waterproofing of roofs,
- products or damp-proof insulation of buildings, underground parts, which are the subject to fire reaction test (Type A),
- products for damp-proof insulation of buildings, underground parts (Type A).

3. The manufacturer:

NEXLER sp. z o.o.
ul. Łużycka 6, 81-537 Gdynia, Poland
tel., fax +48 58 781 45 85
e-mail: info@nexler.com

4. Systems of assessment and verification of constancy of performance:

system 2+ – for the applications: b, d
system 3 – for the applications: a, c,

5. Harmonized standard:

- EN 13707:2004+A2:2009
- EN 13969:2004 oraz EN 13969:2004/A1:2006

Notified body or notified bodies:

1434 Polish Centre for Testing and Certification
(Polskie Centrum Badań i Certyfikacji)

6. Declared performance:

Essential characteristics	Performance	Harmonized technical specification according to point 5 of DoP
Resistance to external fire exposure	NPD	x
Reaction to fire	Klasa E	x, y
Watertightness	≥ 2 kPa (method A) ≥ 10 kPa (method A)	√ x
Maximum tensile force: - longitudinal - extension	450 ± 150 N/50 mm (4 ± 2) %	x, y
- transversal - extension	300 ± 150 N/50 mm (4 ± 2) %	
Resistance to root penetration	NPD	x
Resistance to static loading	NPD	x
	≥ 5 kg (method B)	y
Resistance to impact	NPD	x
	≥ 600 mm (method A)	y
Resistance to Tearing: -longitudinal -transversal	150 ± 100 N 100 ± 50 N	x, y
Resistance of the joint: - peel	NPD	x
	NPD	√
- shear:	300 ± 150 N/50 mm 450 ± 150 N/50 mm	y
- longitudinal - transversal		
Durability	NPD	x
- durability after artificial ageing, watertightness	≥ 2 kPa (method A)	y
- durability against chemical	acc. annex of A standard	
Flexibility	≤ -20°C	x
Flexibility in low temperature	≤ -20°C	y
Dangerous substances	NPD	x, y

The performance of the product identified above are consistent with a set of declared performance. This declaration of performance is issued in accordance with Regulation (EU) no 305/2011 the sole responsibility of the producer referred to above.

Signed on behalf of the manufacturer:

Konrad Liberda


Konrad Liberda

Gdynia, 15.02.2024

